# D-Net<sup>™</sup> 6550

Low trajectory (14deg) ½" impact sprinkler with unique 3D arm for under canopy irrigation and areas with winds.





0000

Very high water distribution uniformity



Robust & long lasting



Reduced labor cost

**Applications** 



Windy open field crop & vegetable irrigation



Under canopy irrigation as Banana



Roof cleaning

## / Benefits & Features

→ High water distribution uniformity & higher yield

Innovative 3D diffusion arm, ensures relatively high water distribution uniformity, resulting uniform crop yields

The lower trajectory angle of the water prevents evaporation to the air in areas with winds, and guarantees maximum water-use efficiency

→ Robust product & long lasting performances D-Net  $^{\text{\tiny{M}}}$  6550 has a special design that makes the sprinkler resistant to wear and ensures high performance throughout the long product life

→ Reduced labor cost & easy maintenance

Versatile installation. Can be installed on solid sets or on removable field stands

Easy to maintain. A special nozzle design, allows simple cleaning of the nozzle even under pressure

D-Net $^{\text{\tiny{M}}}$  6550 is made of UV-protected materials, making it durable under all climate conditions and with any applied





### / Specifications & Recommendations

- ½" impact sprinkler with unique 3D arm and 14degrees water trajectory angle, for full coverage installation with spacing up to 12x12 meters
- 3 different flow rates: 355, 400, 510l/h
- ✓ Nominal flow rate at: 2.5bar
- ✓ Recommended pressure range: 2.0 3.0bar
- ✓ Water Trajectory angle: 14degrees
- Water distribution is achieved by a single front nozzle

- ✓ 1 type of inlet connector: ½" male threaded
- Color coded of the nozzle for easy identification of the flow rate
- Made of UV-protected materials, durable to all climate conditions and nutrients injected in agricultural applications
- Recommended filtration, according to Netafim's instructions\*

\*Note: Filtration method shall be selected based on the type and concentration of the dirt particles contained in the water. Wherever sand exceeding 2ppm exists in the water, a Hydrocyclone shall be installed before the main filter. Wherever sand/ silt/ clay solids exceed 100ppm, pre-treatment shall be applied according to Netafim™ instructions

#### → Technical Data

Nozzle		Working	Flow	Wetted	Precipitation (mm/h)					
Size (mm)	Code Color	Pressure (Bar)	Rate (I/h)	Diameter* (m)	Spacing (m x m)					
					9 x 9	9 x 10	10 x 10	10 x 11	10 x 12	12 x 12
		2.0	318	16	3.9	3.5	3.2	2.9	2.7	2.2
2.3	Grey	2.5	355	17	4.4	3.9	3.6	3.2	3.0	2.5
		3.0	389	17	4.8	4.3	3.9	3.5	3.2	2.7
	Purple	2.0	358	16	4.4	4.0	3.6	3.3	3.0	2.5
2.5		2.5	400	18	4.9	4.4	4.0	3.6	3.3	2.8
		3.0	438	18	5.4	4.9	4.4	4.0	3.7	3.0
2.9	Orange	2.0	456	17	5.6	5.1	4.6	4.1	3.8	3.2
		2.5	510	18	6.3	5.7	5.1	4.6	4.3	3.5
		3.0	559	19	6.9	6.2	5.6	5.1	4.7	3.9

<sup>\*</sup> at least 0.5mm/h

#### → Packaging Data

Model	Quantity P/Box Unit	Box Size (cm x cm x cm)	Box Weigth (kg)	Boxes P/Pallet	Total Units P/Pallet	Pallet Weigth (kg)
D-Net™ 6550	168	54 x 36 x 33	12.0	18	3024	240

#### → Catalog Numbers

Nozzle Size (mm)	Code Color	Flow Rate (I/h) *	Catalog Number
2.3	Grey	355	60100-002300
2.5	Purple	400	60100-002310
2.9	Orange	510	60100-002320

<sup>\*</sup>Nominal flow rate at 2.5bar working pressure

#### → D-Net<sup>™</sup> 6550 Nozzles

Product Illustration	Nozzle Size (mm)	Qty. Per Box	Code Color	Catalog Number Per Box*
8	2.3	350	Grey	60101-000826
4	2.5	350	Purple	60101-000827
*	2.9	350	Orange	60101-000828

<sup>\*</sup>The catalog number is for full box of nozzles





<sup>\*\*</sup> Performance table prepared under laboratory conditions, sprinkler head at 0.5meter above ground

### → Sprinklers Stands & Complementary Products

Product Illustration	Description	Catalog Number			
Vegetable Stand					
U	IMP SPRINKLER STAND 9*12 120CM W/O STK F&S PE	64520-004900			
U	IMP SPRINKLER STAND 9*12 120CM W/O STK F&S FLX	64520-004910			
NetaStand™ Base	<u> </u>				
94	BASE NETASTAND™ FEMALE THREAD ½"-24/CAR: BASE FOR ½" RISER Order by box: 1 box contain 24 units	60101-000900			
4	BASE NETASTAND™ FEMALE THREAD ¾" 24/CAR: BASE FOR ¾" RISER.  Order by box: 1 box contain 24 units	60101-000901			
Riser					
	MEGA-RISER ½"- 0.4MLENGTH - ½" MTH - ½" FTH	64520-002490			
	PLASTIC RISER ¾" MALE FEMALE THREAD 40CM COMPLETE	60101-000650			
Adapters For NetaStand™ P	PE				
	NETASTAND™ ADAPTOR PE 50MM	60101-000935			
	NETASTAND™ ADAPTOR PE 63MM	60101-000936			
Pre-Cut FlexNet™ And Adaptors For NetaStand™ FlexNet™					
_	NETASTAND™ 9M FXN HPPP 2" W/ 2"CONC 120 SETS/PALLET	60101-000964			
	NETASTAND™ 10M FXN HPPP 2" W/2"CONC 120 SETS/PALLET	60101-000965			
	NETASTAND™ 12M FXN HPPP 2" W/2"CONC 120 SETS/PALLET	60101-000966			
-	NETASTAND™ PLUG	60101-000953			

For additional information on sprinklers stands and assembly instructions please review "Sprinklers Stands" section



